



Gold Series Auger Drives

Digga has been designing and manufacturing post hole diggers in Australia for over 30 years. Our product quality and innovation leads the industry.

Features

- Australian Made Quality
- Low maintenance
- 5 year gearbox and 3 year motor warranty
- Fully serviceable gearbox
- 2 Piece shaft, lifetime pullout warranty

Machine Suitability

Skid Steer Loaders and Mini Excavators up to 3 tonne with flows of 35-75 lpm

LIMITED EDITION
UNTIL SOLD OUT

FROM **\$1,750⁺** +GST

INCLUDES SINGLE PIN HITCH

- ADD \$100 FOR FIXED MULTI FIT FRAME
- ADD \$100 FOR DOUBLE PIN HITCH
- ADD \$195 FOR STANDARD SIDE SHIFT FRAME

Model	GOLD SERIES 3
Min Rec Flow	35 lpm
Max Rec Flow	75 lpm
Max Torque (Nm) @ 240 bar	3,578
Pressure Valve Fitted	NA
Max Pressure (Bar)	Do not exceed 240 Bar @ 60 lpm
Max Flow (lpm)	Do not exceed 70 lpm @ 200 Bar
Power (Kw)	Do not exceed 25 Kw (34HP)
Overall Length (mm)	587mm
Diameter (mm)	219mm
Weight (No linkage and hitch)	48kg
STD Output Shaft	65mm Round
Swing Control (SCS)	NA
Diggalign (Auger Alignment)	NA
Recommended Auger Diameter	
Recommended Auger	A4
Max Auger Dia Earth*	600mm

OUTPUT SPEED AND TORQUE

GOLD SERIES 3			
Output Speed		Output Torque	
Lpm	RPM	Bar	Nm
35	38	34	511
40	43	62	920
45	48	103	1,534
50	54	145	2,147
55	59	186	2,700
60	64	214	3,169
65	70	241	3,578
70	75		
75	81		

Output speed and torque specifications are THEORETICAL. Speed and torque output are dependent on the overall system efficiencies associated with the prime movers hydraulic system. This document should be used for information and comparative purposes only. When determining criteria, & application specific information is required, please contact DIGGA.

*TERMS AND CONDITIONS APPLY. INCLUDES DRIVE UNIT, HOSES AND COUPLERS, SINGLE PIN HITCH. UNTIL SOLD OUT



Gold Series Auger Drives

Digga has been designing and manufacturing post hole diggers in Australia for over 30 years. Our product quality and innovation leads the industry.

Features

- Australian Made Quality
- Low maintenance
- 5 year gearbox and 1 year motor warranty
- Fully serviceable gearbox
- 2 Piece shaft, lifetime pullout warranty

Machine Suitability

Skid Steer Loaders and Mini Excavators
up to 2 tonne with flows of 20-50 lpm

**LIMITED
EDITION
UNTIL SOLD OUT**

FROM **\$1,600*** + GST

INCLUDES SINGLE PIN HITCH

- ADD \$100 FOR FIXED MULTI FIT FRAME
- ADD \$100 FOR DOUBLE PIN HITCH
- ADD \$195 FOR STANDARD SIDE SHIFT FRAME

Model	GOLD SERIES
Min Rec Flow	20 lpm
Max Rec Flow	50 lpm
Max Torque (Nm) @ 200 bar	1,513
Pressure Valve Fitted	NA
Max Pressure (Bar)	Do not exceed 200 Bar @ 45 lpm
Max Flow (lpm)	Do not exceed 60 lpm @ 155 Bar
Power (Kw)	Do not exceed 15 Kw (20HP)
Overall Length (mm)	544mm
Diameter (mm)	219mm
Weight (No linkage and hitch)	34kg
STD Output Shaft	65mm Round
Swing Control (SCS)	NA
Diggalign (Auger Alignment)	NA
Recommended Auger Diameter	
Recommended Auger	A4
Max Auger Dia Earth*	400mm

OUTPUT SPEED AND TORQUE

GOLD SERIES			
Output Speed		Output Torque	
Lpm	RPM	Bar	Nm
20	42	34	261
25	53	55	417
30	63	76	574
35	74	117	887
40	84	138	1,043
45	95	166	1,252
50	105	200	1,513

Output speed and torque specifications are THEORETICAL. Speed and torque output are dependent on the overall system efficiencies associated with the prime movers hydraulic system. This document should be used for information and comparative purposes only. When determining criteria, & application specific information is required, please contact DIGGA.

*TERMS AND CONDITIONS APPLY. INCLUDES DRIVE UNIT, HOSES AND COUPLERS, SINGLE PIN HITCH. UNTIL SOLD OUT